

SKG-IKOB PRODUCTCERTIFICATE

404.211.01

Date of issue: 20-06-2022



Certificate holder

Fuhr GmbH & Co KG
Carl Fuhr Straße 12
D-42579 Heiligenhaus
T: +49 (0) 2056 5920
E: info@fuhr.de
I: www.fuhr.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

cylinder mortice multipointlock wo electromechanical

delivered under logo / brand:

FUHR

delivered under type- and / or article number:

855(GL) / 856 / 859 / 869 - type 3-SKG2

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink handwritten signature, appearing to be "H.A.J. van Dartel", written over a light blue horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Fuhr GmbH & Co KG
Number: 404.211.01

page 2 of 2

1. PRODUCT

cylinder mortice multipointlock wo electromechanical

PRODUCT TYPE

multipoint lock

2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electrical operation
Construction:	1 forend with (for-elderly) lock with square bolt and var. type latches + 2 additional hook bolts with or without rollbolts
System:	key or handle operated / self-locking OR electronic operated lockable by 17 mm profile cylinder OR electronic PZ: 92 mm , BS: 35 ~ 80 mm
Material:	forend: steel zinc coated or inox lock cases: steel zinc coated
Dimension:	forend PVC: 1546/2405 mm whether OR not connectable x(U)16~30 mm forend Aluminium: 1546/2405 mm whether OR not connectable x(U)20~30 mm lock cases: 200xdm+18x15 mm / 95~135 mm x 35~40 mm x 15 mm
Fixing:	forend in PVC: 4 mm in steel reinforcement min. 1,5 mm forend in ME: 4 mm or M5 with plate (Wicona)
Intended use:	PVC, metal, door-inward-opening, door-outward-opening for doors in combination with FUHR box keepers or keeperstrip: PVC: 404.611.01 OR metaal: 404.611.05

3. DELIVERY

The delivery includes an installation instruction:
1-0800-008 OF 1-0800-006 OF 1-0800-025

4. PERFORMANCES

A cylinder mortice multipointlock wo electromechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this cylinder mortice multipointlock w/o electromechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this cylinder mortice multipointlock w/o electromechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).